


Dots DISE  
SCALE 10:1

PIN CONNECTION

1	CSB
2	RES
3	NC
4	SCL
5	SDA
6	VSS
7	VDD
8	VOUT
9	CAP3N
10	CAP3P
11	CAP1N
12	CAP1P
13	CAP2P
14	CAP2N
15	CAP4P
16	VO

- NOTE:
1. DISPLAY TYPE:FSTN
  2. DRIVING METHOD: 1/49 DUTY, 1/8 BIAS
  3. OPERATING VOLTAGE: VDD=3.0V,VOP=8.5V
  4. OPERATING TEMP: -10° ~ 60°C
  5. STORAGE TEMP: -20° ~ 70°C
  6. VIEWING DIRECTION: 12 O'CLOCK
  7. POLARIZER MODE: TRANFLECTIVE/POSITIVE
  8. CONNECTION:COG+FPC (小片在上, 磨边)
  9. IC:ST7588Ti-G,3-line(8bit)serial interface A mode
  10. Dimensions with ark asterisk"\*are important, with ark bracket"()"are referenced;
  11. DIMENSIONS ARE IN MILLIMETERS AND UNLESS OTHERWISE NOTED ARE ±0.20MM
  12. THE TOTAL THICKNESS OF GLASS IS NOT INCLUDING THE PROTECTIVE FILM.



Block Diagram

REVISES		SUN-VIEW TECHNOLOGY CO., LTD						
CONTENT								
02	增加重點尺寸標示	CUSTOM					PROJECTION	
		DRAWING BY	鄧秀玉	2018.11.26	ITEM	MD	UNITS	mm
		CHECKED BY			CODE	MD130515002	SCALE	
		APPROVED BY			MODEL	SVG128048BWN	SHEET	1 OF 5