



Interface pin connection

PIN NO.	1	2	3	4	5	6	7	8
SYMBOL	VSS	VDD	V0	RS	R/w	E	DB0	DB1
PIN NO.	9	10	11	12	13	14	15	16
SYMBOL	DB2	DB3	DB4	DB5	DB6	DB7	N.C	N.C

- NOTE:
1. DISPLAY TYPE:STN(YELLOW-GREEN)
 2. DRIVING METHOD: 1/16 DUTY, 1/5 BIAS
 3. OPERATING VOLTAGE: VDD-V0=4.5V,VDD=5.0V
 4. OPERATING TEMP: 0° ~ 50°C
 5. STORAGE TEMP: -20° ~ 70°C
 6. VIEWING DIRECTION: 6 O'CLOCK
 7. POLARIZER MODE: TRANSFLECTIVE/POSITIVE
 8. CONNECTION: COB
 9. CONTROLLER IC:ST7066U(SITRONIX)
 10. LED COLOR:YELLOW-GREEN
 11. DIMENSIONS ARE IN MILLIMETERS AND UNLESS OTHERWISE NOTED ARE ±0.20MM

REVISES	SUN-VIEW TECHNOLOGY CO., LTD							
CONTENT								
02	增加重點尺寸標示	CUSTOM					PROJECTION	
	DRAWING BY	沈光娥	2018.11.26	ITEM	MD	UNITS	mm	
	CHECKED BY			CODE	MD040316002	SCALE		
	APPROVED BY			MODEL	SVC016001LYLB	SHEET	1 OF 1	