



透明PET組成			
供應商	型番	名稱	備考
TORAY	Lumirror T60	Lumirror	材質: PET t=0.188 透明
3 M	467	雙面膠	t=0.06

- NOTE:
1. DISPLAY TYPE:FSTN
 2. DRIVING METHOD: 1/65 DUTY, 1/9 BIAS
 3. OPERATING VOLTAGE:VDD-V5=9.5V,VLED=4.7~5.3V
 4. OPERATING TEMP: 0° ~ 50°C
 5. STORAGE TEMP: -20° ~ 70°C
 6. VIEWING DIRECTION: 6 O'CLOCK
 7. POLARIZER MODE: TRANSMISSIVE/POSITIVE
 8. CONNECTION:COG+BL+FPC (小片在上, 磨边)
 9. LED BACKLIGHT COLOR:WHITE
 10. CONTROLLER/DRIVER IC:NJU6655B
 11. DIMENSIONS ARE IN MILLIMETERS AND UNLESS OTHERWISE NOTED ARE ±0.20MM
 12. THE TOTAL THICKNESS OF GLASS IS NOT INCLUDING THE PROTECTIVE FILM.

REVISES CONTENT		CUSTOM				PROJECTION		UNITS	
06	增加重點尺寸標示	DRAWING BY	沈光娥	2018.11.19	ITEM	MD	SCALE	mm	
		CHECKED BY			CODE	MD270415003	SHEET	1:1	
		APPROVED BY			MODEL	SVG160064AWDC	SHEET	1 OF 2	

SVT® SUN-VIEW TECHNOLOGY CO., LTD