



DOT DETAIL

Pin No.	Symbol
1	V0IN
2	V0OUT
3	V1
4	V2
5	V3
6	V4
7	VLCD
8	C4P
9	C2N
10	C2P
11	C1P
12	C1N
13	C3P
14	VDDA
15	VSS
16	VDD
17	XCS
18	RST
19	E
20	D7
21	D6
22	D5
23	D4
24	D3
25	D2
26	D1
27	D0
28	RW
29	A0
30	VDD

NOTE :

1. LCD : FSTN TYPE, TRANFLECTIVE MODE POSITIVE
2. VIEWING DIRECTION : 6 O'CLOCK
3. TOP : -10~60°C ; Tst : -20~70°C
4. TOLERANCE FOR NOT ASSIGNED : ±0.2 mm
5. LSI : ST7529-G
6. THE MINIMUM BENDING RADIUS OF THE FPC IS 2.0 mm
7. LCD : VDD-VSS=3.3V 1/120 DUTY 1/9 BAIS
- 8.THERE IS NO BLEEDING OUTSIDE THE VIEW AREA.

REVISES CONTENT		SUN-VIEW TECHNOLOGY CO., LTD						
03	修改瑪拉膠帶形狀及增加備註	CUSTOM	沈光娥	2018.12.26	ITEM	LCM	PROJECTION	
		DRAWING BY			CODE	MD050515001	UNITS	mm
		CHECKED BY			MODEL	SVG255084AWNC	SCALE	1:1
		APPROVED BY					SHEET	1 OF 4