



PIN	NAME
1	GND
2	VLCD
3	VS+
4	VS-
5	VB0-
6	VB1-
7	VB1+
8	VB0+
9	VDD
10	VSS
11	TST4
12	BM0
13	CS0
14	CD
15	WR1
16	WR0
17	RST
18	D0
19	D1
20	D2
21	D3
22	D4
23	D5
24	D6
25	D7
26	GND
27	A
28	K1
29	K2
30	K3

- NOTE:
1. DISPLAY TYPE:DFSTN
 2. DRIVING METHOD: 1/160 DUTY, 1/14 BIAS
 3. OPERATING VOLTAGE: 14.0 VOP
 4. OPERATING TEMP: -10° ~ 60°C
 5. STORAGE TEMP: -20° ~ 70°C
 6. VIEWING DIRECTION: 12 O'CLOCK
 7. POLARIZER MODE: TRANSMISSIVE/NEGATIVE
 8. CONNECTION: FPC<Edge>
 9. IC:UC1698U
 10. DIMENSIONS ARE IN MILLIMETERS AND UNLESS OTHERWISE NOTED ARE ±0.20MM

REVISES CONTENT		 SUN-VIEW TECHNOLOGY CO., LTD							
12	Increase key size indication	CUSTOM						PROJECTION	
		DRAWING BY	沈光娥	2018.10.31	ITEM	LCM	UNITS	mm	
		CHECKED BY			CODE	MD020216001	SCALE	1:1	
		APPROVED BY			MODEL	SVG320160AFDC	SHEET	1 OF 4	